

NS8004-NTP

Product Specification GNSS Locked NTP Server and Timing Reference



GNSS locked reference provides accurate timing over direct and network connections.

Two digital outputs are user selectable between IRIG-B and PPS.

One analog output is user selectable between PPS, low phase noise 10MHz and a configurable square wave frequency between 10Hz and 50MHz.

Key Features:



- NTP Server
- PPS: +/- 10ns
- +/-150ns sync accuracy to UTC
- 10MHz sine
- IRIG-B DCLS
- IRIG AM
- Have Quick
- 10Hz – 50MHz square wave
- LVTTTL
- LVDS
- NMEA
- DC powered (9-48 VDC)

Technical Specifications

Analog Signal	
Number of Outputs	2
Signal Options	10MHz (Low Phase Noise), PPS, 10Hz-50MHz Square Wave, IRIG AM, Have Quick
Load Impedance	50 Ohms
Connector	SMA
10MHz Output	
Amplitude	1 VRMS ± 0.2
Locked stability	5E-11
First year frequency stability	+/-40 ppb (unlocked)
Temperature stability	+/-100 ppb (unlocked)
10.0 MHz Phase Noise (dBc/Hz)	
1 Hz	-60
10 Hz	-90
100 Hz	-100
1 kHz	-120
10 kHz	-130
100 kHz	-140
PPS Output	
Amplitude	3.3 VDC CMOS
Accuracy	50ns RMS
Pulse width	Programmable 1 to 500ms in 1 μ sec steps
Rise time	<5 ns
10Hz-50MHz Square Wave	
Amplitude	3.3 VDC CMOS

Digital Signals	
Number of Outputs	2
Signal Options	PPS, IRIG-B DCLS, 10Hz – 50MHz Square Wave, LVTTTL, LVDS
Load Impedance	1k Ohm
Connector	Keyed 4 pin connector
PPS	
Amplitude	3.3 VDC CMOS
Accuracy	50ns RMS
IRIG-B	
Output	3.3V DCLS
Format	Enabled/Disable: Year, SBS, or IEEE1344 bits

NTP/SNTP	
Version	NTPv4
Accuracy	+/- 200 ns



GNSS Receiver

Number of Channels	72
Cold Start Acquisition	<30 seconds

Receiver Sensitives(dBm)

Tracking	-167
Reacquisition	-160
Cold Start	-148
Hot Start	-157

Supported Signals

GPS	L1C/A
GLONASS	L1OF
Galileo	E1-B/C
BeiDou	B1I

Antenna




Supply Voltage	3.3V
----------------	------

Front panel Indicators and Control

Status Indicator LEDs	LEDs indicate GNSS lock and NTP operation
Remote interface	
Rear Panel Serial Port	USB mini-B to serial interface for system status and system configuration 115200 baud default with NMEA out
Standard Serial Baud Rates	Selectable baud rate 19200, 38400, 57600 or 115200 (default), 8 data bits, 1 stop bit, no parity, no flow control
Network Connectivity	Ethernet: 10/100MB RJ-45 Rear panel
Power	
DC input	+/- 9-48VDC 10W

Environmental and Mechanical

Mechanical	
Height	1.13" (28.68mm)
Width	3.5" (88.90mm)
Depth	5.57" (141.49mm)
Weight	1.0 lb.
Environmental	
Operating temperature	-10 to 65°C
Storage temperature	-40 to 70°C
Humidity	0% - 90% RH non-condensing
Agency Certifications	UL / FCC Part 15
EU compliance	RoHS, REACH, WEEE
EMC Compliance Emissions/Immunity	CISPR 32 Emissions CISPR 35 Immunity IEC 61000-4-2 ESD IEC 61000-4-3 Radiated IEC 61000-4-4 Transient/burst immunity IEC 61000-4-5 Surge immunity IEC 61000-4-6 Immunity to conducted
Safety	UL 62368-1



This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Revision History

Date	Nature of Changes	Approved By
260210	Initial release.	Ethan Bozarth
260506	Added outputs, signals, block diagram, copy	Daniel Longo
260611	Updated models and dimensions	Daniel Longo
260806	Updated models and dimensions	Daniel Longo



All information provided herein is the property of Novus Power Products LLC. The information included may be reproduced for the purpose of operating the Novus equipment. Subject to change.
This document is copyright © 2025 - 2026 Novus Power Products LLC. All rights reserved.